




# Up to 3xL18 Rigging System





## **Contents:**



(a): The type of screws may differ from the representation


Weight: 26.5 kg / 58.5 lb



- Read this document before using.
- Keep this document.
- Observe all warnings and cautions.



### **Dimensions:**



For fixation, you have the choice between M8 and M10

## **WARNINGS**


Ensure that the mounting location and fasteners can support at least 4 times the weight of all the installed cabinets, auxiliary equipment and cables.

Use only the provided screws (thread lock coated) and accessories.


### Implementation of L18

Prepare the Main plates by screwing the M10x30 screws on the holes (see picture below), do not tighten completely and leave at least 6mm.

Assemble the L18 Plates on each side of L18 using the M10x20 screws.








- Keep this document.

- Observe all warnings and cautions.



## Assembly on the ceiling plate



# LNI-3L18 frame tilt (+/- 1°)

	Holes 1	Holes 2	Holes 3	Holes 4	Holes 5	Holes 6	Holes 7
2x L18	10°	5°	2°	1°	-1°	-6°	-8°
3x L18	12°	6°	3°	0°	-2°	-7°	-11°

Note 1: Holes 1 are those toward F.O.H.

Note 2: All angles measurements have been done without cables weight.

Note 3: Angles are in relation to Horizontal position (0°)





- NEXO cannot accept responsibility for accidents caused by any factor other than defects in this product itself.
- Please check the web site <u>nexo-sa.com</u> for the latest update.





- Keep this document.Observe all warnings and cautions.

